

bizhub 361i Black & White A3 multifunctional









CUSTOMER BENEFITS



Secure network integration, data encryption, storage drive overwrite, and advanced user authentication



Productivity

Reliability, high-speed scanning and printing, combined with powerful finishing functions



Sustainability

Numerous eco features reduce energy consumption and costs



Intuitive operability

Operate the bizhub like a smartphone or tablet with fully customised user interface



Application ecosystem

Enhanced efficiency thanks to Konica Minolta's extensive applications portfolio




ServicesEfficient printer fleet management, including automatic con-sumables delivery, pro-active maintenance and remote setup

х2

OR

OR

OPTIONS



Document converter pack LK-110v2 ThinPrint® client

Trusted Platform Module

Antivirus



2 CONNECTIVITY Fax board FK-514

Wireless LAN UK-221 USB I/F kit

USB I/F kit

Card authentication

Mount kit



3 OTHERS

Document feeder DF-714

Working table

Offline Stapler

10-Key pad Security kit

Replacement SSD EM-908

Keyboard holder KH-102 Air cleaning unit CU-102 4 MEDIA INPUT

Intelligent media sensor 2x Universal tray Large capacity tray PC-416

Large capacity tray PC-417 Copier desk DK-516

Large capacity tray

Banner tray MK-730

MEDIA OUTPUT

Job separator

Inner finisher FS-533

OR

Staple finisher FS-539

Relay unit RU-513

Booklet finisher

Relay unit RU-513 Punch kit for FS-539/SD PK-524

LEGEND Mandatory option

Option

This option can only be installed with the respective option above it

FINISHING FUNCTIONALITIES











Duplex



















stapling

stapling

punching

punching

mixplex/

Half-fold

insertion

Letter-fold

Booklet

Offset sorting

printing

Stapling (offline)

DESCRIPTION

ENHANCED FEATURES	
LK-104v3 Voice Guidance	Enables easy to follow audio guidance for visually impaired users
	Requires KP-102
LK-105v4 OCR text recognition	Searchable PDF and PPTX
LK-106 Barcode fonts	Supports native barcode printing
LK-107 Unicode fonts	Supports native Unicode printing
LK-108 OCR A and B fonts	Supports native OCR A and B font printing
LK-110v2 Document converter pack	Generates various file formats incl. DOCX, XLSX and PDF/A
LK-111 ThinPrint® client	Print data compression for reduced network impact
LK-115v2 Trusted Platform Module	Trusted Platform Module for protection of data encryption and
	decryption
LK-116 Antivirus	Bitdefender® antivirus provides real time scanning of all
	incoming and outgoing data
CONNECTIVITY	
FK-514 Fax board	Super G3 fax, digital fax functionality
UK-221 Wireless LAN	Wireless LAN and wireless LAN Access Point Mode
EK-608 USB I/F kit	USB keyboard connection
EK-609 USB I/F kit	USB keyboard connection; Bluetooth
ID card reader	Various ID card technologies
MK-735 Mount kit	Installation kit for HID card readers

OTHERS	
DF-632 Document feeder	Reversing automatic document feeder, capacity 100 originals
DF-714 Document feeder	Dualscan automatic document feeder, capacity 100 originals
WT-506 Working table	Authentication device and Offline stapler placement
FS-P04 Offline Stapler	Offline stapler, 20 sheets stapling
KP-102 10-Key pad	For use instead of touchscreen
SC-509 Security kit	Copy guard function
EM-908 Replacement SSD	1 TB SSD to increase storage space
KH-102 Keyboard holder	To place USB keyboard
CU-102 Air cleaning unit	Improving indoor air quality by reduced emission
MEDIA INPUT	
IM-103 Intelligent media sensor	Autodetects paper weight and type
PC-216 2x Universal tray	2x 500 sheets, A5-A3, 52-256 g/m ²
PC-416 Large capacity tray	2,500 sheets, A4, 52-256 g/m ²
PC-417 Large capacity tray	1,500 + 1,000 sheets, A5-A4, 52-256 g/m ²
DK-516 Copier desk	Provides storage space for print media and other materials
LU-302 Large capacity tray	3,000 sheets, A4, 52-256 g/m ²
MK-730 Banner tray	Multipage banner feeding
MEDIA OUTPUT	
S-506 ob separator	Separation of fax output; etc.
FS-533 Inner finisher	50-sheet stapling, 500 sheets max. output
PK-519 Punch kit for FS-533	2/4 hole punching, autoswitching
FS-539 Staple finisher	50 sheets stapling; 3,200 sheets max. output
FS-539SD Booklet finisher	50 sheets stapling; 20 sheets booklet finisher;
	2,200 sheets max. output
PK-524 Punch kit for FS-539/SD	2/4 hole punching; autoswitching
RU-513 Relay unit	For FS-539/SD installation
•	

TECHNICAL SPECIFICATIONS

Sustam speed A4	Unito 26 nom
System speed A4	Up to 36 ppm
System speed A3	Up to 18 ppm
Autoduplex speed A4	Up to 36 ppm
1st page out time A4	4.6 sec.
Warm-up time	Approx. 11 sec. ¹
Imaging technology	Laser
Toner technology	Simitri® V polymerised toner
Panel size/resolution	10.1" / 1024 x 600
System memory	8 GB (standard/max)
System hard drive	256 GB SSD (standard) / 1 TB SSD (optional)
Interface	10/100/1,000-Base-T Ethernet; USB 2.0;
	Wi-Fi 802.11 b/g/n/ac (optional)
Network protocols	TCP/IP (IPv4 / IPv6); SMB; LPD; IPP; SNMP; HTTP(S); Bonjour
Automatic document feeder	Up to 100 originals; A6-A3; 35-163 g/m²; RADF or Dualscan ADF
(optional)	available
ADF double feed detection	Standard (with dualscan ADF)
Printable paper size	A6-SRA3; customised paper sizes;
	banner paper max. 1,200 x 297 mm
Printable paper weight	52-300 g/m ²
Paper input capacity	1,150 sheets / 6,650 sheets (standard/max)
Paper tray input (standard)	1x 500; A6-A3; custom sizes; 52-256 g/m ²
	1x 500; A5-SRA3; custom sizes; 52-256 g/m ²
Paper tray input (optional)	2x 500 sheets; A5-A3; 52-256 g/m ²
	1x 2,500 sheets; A4; 52-256 g/m ²
	1x 1,500 + 1x 1,000 sheets; A5-A4; 52-256 g/m ²
Large capacity tray (optional)	1x 3,000; A4; 52-256 g/m ²

CVCTEM	SPECIFICATIONS	
JIJILIVI	3F LUII IUMI IUM3	

Manual bypass	150 sheets; A6-SRA3; custom sizes, banner; 60-300 g/m ²
Finishing modes (optional)	Offset; Group; Sort; Staple; Staple (offline); Punch; Half-fold;
	Letter-fold; Booklet
Automatic duplexing	A6-SRA3; 52-256 g/m ²
Output capacity	Up to 250 sheets / up to 3,300 sheets (standard/max)
Stapling	Max. 50 sheets or 48 sheets + 2 cover sheets (up to 209 g/m²)
Stapling output capacity	Max. 100 sets
Letter fold	Max. 3 sheets
Letter fold capacity	Max. 30 sets; unlimited (without tray)
Booklet	Max. 20 sheets or 19 sheets + 1 cover sheet (up to 209 g/m²)
Booklet output capacity	Max. 20 booklets; unlimited (without tray)
Power consumption	220-240 V / 50/60 Hz; Less than 1.58 kW
System dimension (W x D x H)	615 x 688 x 1165 mm (with optional paper cabinet)
System weight	Approx. 100.0 kg (with optional paper cabinet)

PRINTER SPECIFICATIONS

Print resolution	1,800 (equivalent) x 600 dpi; 1200 x 1200 dpi
Page description language	PCL 6 (XL3.0); PCL 5c; PostScript 3 (CPSI 3016); XPS

Operating systems	Windows 10 (32/64); Windows 11; Windows Server 2012;
	Windows Server 2012 R2; Windows Server 2016;
	Windows Server 2019; Windows Server 2022;
	macOS 10.14 or later; Unix; Linux; Citrix
Printer fonts	80 PCL Latin; 137 PostScript 3 Emulation Latin
Mobile printing	AirPrint (iOS); Mopria (Android);
	Konica Minolta Mobile Print (iOS/Android)
	optional: WiFi Direct
SCANNER SPECIFICATIONS	
Scan speed	Up to 100/100 ipm in simplex (mono/colour)
•	Up to 200/200 ipm in duplex (mono/colour)
Scan resolution	Up to 600 x 600 dpi
Scan modes	Scan-to-eMail (Scan-to-Me); Scan-to-SMB (Scan-to-Home);
	Scan-to-FTP; Scan-to-Box; Scan-to-USB; Scan-to-WebDAV;
	Scan-to-DPWS; Scan-to-URL; TWAIN scan
File formats	JPEG; TIFF; PDF; Compact PDF; Encrypted PDF; XPS; Compact XPS;
	PPTX; PDF/A 1a and 1b
	optional: Searchable PDF; Searchable DOCX/PPTX/XLSX
Scan destinations	2,000 destinations + 100 groups; LDAP support
COPIER SPECIFICATIONS	
	600 x 600 dpi
Copy resolution	
Copy resolution Gradation	256 gradations
	·
Gradation	256 gradations
Gradation Multicopy	256 gradations 1-9,999
Gradation Multicopy Original format Magnification	256 gradations 1-9,999 Max. A3
Gradation Multicopy Original format Magnification FAX SPECIFICATION	256 gradations 1-9,999 Max. A3 25-400% in 0.1% steps; Auto-zooming
Gradation Multicopy Original format Magnification FAX SPECIFICATION Fax standard	256 gradations 1-9,999 Max. A3 25-400% in 0.1% steps; Auto-zooming Super G3 (optional)
Gradation Multicopy Original format Magnification FAX SPECIFICATION Fax standard Fax transmission	256 gradations 1-9,999 Max. A3 25-400% in 0.1% steps; Auto-zooming Super G3 (optional) Analogue; i-Fax; Colour i-Fax; IP-Fax
Gradation Multicopy Original format Magnification FAX SPECIFICATION Fax standard Fax transmission Fax resolution	256 gradations 1-9,999 Max. A3 25-400% in 0.1% steps; Auto-zooming Super G3 (optional) Analogue; i-Fax; Colour i-Fax; IP-Fax Up to 600 x 600 dpi
Gradation Multicopy Original format Magnification FAX SPECIFICATION Fax standard Fax transmission Fax resolution Fax compression	256 gradations 1-9,999 Max. A3 25-400% in 0.1% steps; Auto-zooming Super G3 (optional) Analogue; i-Fax; Colour i-Fax; IP-Fax Up to 600 x 600 dpi MH; MR; MMR; JBIG
Gradation Multicopy Original format Magnification FAX SPECIFICATION Fax standard Fax transmission Fax resolution	256 gradations 1-9,999 Max. A3 25-400% in 0.1% steps; Auto-zooming Super G3 (optional) Analogue; i-Fax; Colour i-Fax; IP-Fax Up to 600 x 600 dpi
Gradation Multicopy Original format Magnification FAX SPECIFICATION Fax standard Fax transmission Fax resolution Fax compression Fax modem	256 gradations 1-9,999 Max. A3 25-400% in 0.1% steps; Auto-zooming Super G3 (optional) Analogue; i-Fax; Colour i-Fax; IP-Fax Up to 600 x 600 dpi MH; MR; MMR; JBIG Up to 33.6 Kbps
Gradation Multicopy Original format Magnification FAX SPECIFICATION Fax standard Fax transmission Fax resolution Fax compression Fax modem	256 gradations 1-9,999 Max. A3 25-400% in 0.1% steps; Auto-zooming Super G3 (optional) Analogue; i-Fax; Colour i-Fax; IP-Fax Up to 600 x 600 dpi MH; MR; MMR; JBIG Up to 33.6 Kbps
Gradation Multicopy Original format Magnification FAX SPECIFICATION Fax standard Fax transmission Fax resolution Fax compression Fax modem Fax destinations	256 gradations 1-9,999 Max. A3 25-400% in 0.1% steps; Auto-zooming Super G3 (optional) Analogue; i-Fax; Colour i-Fax; IP-Fax Up to 600 x 600 dpi MH; MR; MMR; JBIG Up to 33.6 Kbps
Gradation Multicopy Original format Magnification FAX SPECIFICATION Fax standard Fax transmission Fax resolution Fax compression Fax modem Fax destinations USER BOX SPECIFICATIONS	256 gradations 1-9,999 Max. A3 25-400% in 0.1% steps; Auto-zooming Super G3 (optional) Analogue; i-Fax; Colour i-Fax; IP-Fax Up to 600 x 600 dpi MH; MR; MMR; JBIG Up to 33.6 Kbps 2,000 single + 100 groups

Group (with authentication)

Secure print; Encrypted PDF print; Fax receipt; Fax polling

SYSTEM FEATURES

SISILWITLATURLS	
Security	ISO15408 Common Criteria (in evaluation);
	IP filtering and port blocking;
	SSL3 and TLS1.1/1.2/1.3 network communication; IPsec support
	IEEE 802.1x support; User authentication; Authentication log;
	Secure print; Kerberos;
	Strorage drive data encryption (AES 256); Confidential fax;
	Print user data encryption
	optional: Antivirus realtime scanning (Bitdefender®);
	Copy protection (Copy Guard, Password Copy)
Accounting	Up to 1,000 user accounts; Active Directory support (user name +
	password + e-mail + smb folder); User function access definition;
	Authentication by mobile device (Android)
	ID card authentication (ID card reader);
	Authentication by mobile device (iOS)
Software	Data Administrator; Web Connection; HDD Backup Utility;
	Driver Packaging Utility; Log Management Utility;
	Font Management Utility; Download Manager

¹ Warm-up time may vary depending on the operating environment and usage

- All specifications refer to A4-size paper of 80 g/m² quality.
 The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.

 - The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a
- particular page size (6% coverage of A4). The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and
- Some of the product illustrations contain optional accessories.
- Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
- Konica Minolta does not warrant that any specifications mentioned will be error-free.
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.



Type of system boxes











 $^{^{\}mathrm{2}}$ If the maximum volume is reached within a period of one year, then a maintenance cycle must be performed